

Contractor \_\_\_\_\_  
Approval \_\_\_\_\_  
Contractor's P.O. No. \_\_\_\_\_  
Representative \_\_\_\_\_  
SKU \_\_\_\_\_

**Dormont®**  
A WATTS Brand

# Double and Single SwivelGuard with Standard Snap Quick-Disconnect Kit Assembly

## Ordering Information

		LENGTH		
Configuration	Size I.D.	36" (914mm)	48" (1,219mm)	60" (1,524mm)
Double SwivelGuard Kit*	1/2"	RG502S36	RG502S48	RG502S60
Single SwivelGuard Kit**		RG50S36	RG50S48	RG50S60
Double SwivelGuard Kit*	3/4"	RG752S36	RG752S48	RG752S60
Single SwivelGuard Kit**		RG75S36	RG75S48	RG75S60
Double SwivelGuard Kit*	1"	RG1002S36	RG1002S48	RG1002S60
Single SwivelGuard Kit**		RG100S36	RG100S48	RG100S60

## BTU/hr Flow Capacity Natural Gas (Flow rating BTU/hr 0.64 SP. GR. @ 0.5 inch WC pressure drop)

		LENGTH		
Model	Size I.D.	36" (914mm)	48" (1,219mm)	60" (1,219mm)
RG502S	1/2"	69,000	60,000	54,000
RG50S		72,000	63,000	56,000
RG752S	3/4"	193,000	160,000	140,000
RG75S		203,000	167,000	147,000
RG1002S	1"	336,000	295,000	261,000
RG100S		353,000	310,000	274,000

\***Double SwivelGuard Kits include:** The ReliaGuard gas hose, Double SwivelGuard, Standard Snap, restraining device and full port valve

\*\***Single SwivelGuard Kits include:** The ReliaGuard gas hose, Single SwivelGuard, Standard Snap, restraining device, 90° street elbow and full port valve

## Typical Installation



### The ReliaGuard



The ReliaGuard® is a commercial, moveable-grade gas connector designed for use with moveable equipment.

Moveable equipment is defined in ANSI Standard Z21.69/ CSA 6.16 as gas utilization equipment that may be mounted on casters or otherwise be subject to movement.



### SwivelGuard

- Reduces stress on connector
- Increases kitchen aisle space by allowing connector to be positioned closer to the wall



### Standard Snap

- Quick-disconnect fitting
- Thermal shut-off when internal temperature exceeds 350°F (177°C)



### Restraining Device

- ANSI Z21.69 Standard section 1.7.4 states: Connectors when used on caster-mounted equipment shall be installed with a restraining device, which prevents transmission of the strain to the connector



**We guarantee our commercial gas connectors for 5 years of the original appliance to which it is connected.**



**A WATTS Brand**

**USA:** T: (800) 367-6668 • F: (724) 733-4808 • [Dormont.com](http://Dormont.com)

**Canada:** T: (905) 332-4090 • F: (905) 332-7068 • [Dormont.ca](http://Dormont.ca)

**Latin America:** T: (52) 81-1001-8600 • [Dormont.com](http://Dormont.com)