iceValet®

HD22 - 22" Hotel Dispenser

iceValet® Hotel Dispenser

Features

- Stores up to 120 lb. of cube ice.
- Simple push chute for easy ice dispensing.
- Modern, stylish design in a corrosion resistant metallic cabinet.
- Removable top panel allows access to the bin for easy cleaning without having to remove the ice machine.
- Improved sink depth that will accommodate almost every size hotel ice bucket.
- Equipped with an 11 ft. power cord.
- Match the iceValet[®] dispenser with a Scotsman Prodigy Plus[®] ice machine featuring self-monitoring technology, cost-saving energy efficiency, extended time between cleanings, easy-access servicing and built-in anti-microbial protection. All of these features add up to the smartest choice in ice.

Easy Push Chute







HD22

Application Bin Capacity

120/59 lb/kg



Matching Ice Machine Options

			24 Hr ice Production		
Model Number	Cube Size	Condenser Type	70°F/21°C 50°F/10°C lb/kg	Air Water	90°F/32°C 70°F/21°C lb/kg
C0322MA	Medium	Air	356/162		232/105
C0322MW	Medium	Water	366/166		292/133
C0322SA	Small	Air	356/162		232/105
C0322SW	Small	Water	366/166		292/133
C0522MA	Medium	Air	475/216		340/154
C0522MW	Medium	Water	549/250		409/186
C0522SA	Small	Air	475/216		340/154
C0522SW	Small	Water	549/250		409/186



Polyurethane Insulation

Foam insulation is forced between the wall and liner under heat and pressure to form a perfect wall to wall bond, preserving ice supply for long periods.















- 3 years parts and labor on all components.
- Warranty valid in North, South & Central America for commercial installations.
- Contact factory for warranty in other regions.
- Residential Applications: 1 year parts and labor



- 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •
- 1-800-SCOTSMAN Fax: 847-913-9844 www.scotsman-ice.com customer.relations@scotsman-ice.com •

Installation Note: Allow 6" space at left, back and right side for ventilation and utility connections.






C0322 on HD22 hotel dispenser.

Specifications

Model Number	Actuation	Application Bin Capacity Ib/kg	Electrical	Circuit Wires	Min. Circuit Ampacity	Max. Fuse Size or HACR Circuit Breaker (amps)
HD22B-1	Push	120/59	115/60/1	2	Cord	15





	Minimum	Maximum
Air Temperatures	50°F (10°C)	100°F (38°C)
Water Temperatures	40°F (4.4°C)	100°F (38°C)
Remote Cond. Temps	-20°F (-29°C)	120°F (49°C)
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)
Electrical Voltage	-5%	+10%

Specifications and design are subject to change without notice.

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.



