

Project \_\_\_\_\_  
Item \_\_\_\_\_  
Quantity \_\_\_\_\_  
CSI Section 11400  
Approval \_\_\_\_\_  
Date \_\_\_\_\_

## Models DynaStar



### Standard Features

- Built-in booster heater with Sani-Sure™ final rinse system ensures proper rinse water temperature
- Pumped rinse for consistent rinse pressure
- Adjustable rinse system
  - Econo uses 0.66 gal per rack
  - Turbo uses 0.89 gal per rack
- Automatic tank fill
- Door-actuated start
- Three (3) selectable timed cycles
- Digital LED display
- Onboard digital diagnostics
- Delime cycle
- 17-1/2" (445 mm) vertical chamber clearance
- Triple Wash Arm for consistent reliable washing performance
- Specially designed stainless steel nozzles provide superior cleaning action
- Interchangeable upper and lower wash/rinse arms
- 1 hp stainless steel wash pump motor
- Vent fan control - shuts vent fan off when machine is idle
- Interchangeable scrap baskets
- Low watt density electric wash tank heater
- Hi-limit thermostat and low water protection
- Detergent/rinse additive signal connection fuse box
- Front and side dress panels
- Adjustable bullet feet

### Mandatory Specs

Specify:  
Voltage \_\_\_\_\_

### Options

- ☐ 460V Electrical
- ☐ Single Phase
- ☐ Drain Water Tempering Kit
- ☐ 1/2" Pressure Regulator
- ☐ Scaltrol
- ☐ Water Hammer Arrestor
- ☐ Flanged Feet
- ☐ Security Package

### Accessories

- ☐ 36-Compartment Rack
  - ☐ 4-1/8" tall (105 mm)
  - ☐ 5-5/8" tall (143 mm)
  - ☐ 7" tall (178 mm)
- ☐ Combination Rack
- ☐ Peg Rack

### Specifications

- Uses 0.66 gallons (2.5 liters) of water per rack
- Total automatic (normal) cycle - 58 seconds
- 62 (57)\* racks per hour (normal cycle)
- Built-in 70 °F (38.9 °C) rise booster heater
- 1 hp stainless steel wash pump motor
- Single point connections for all utilities
- Adjustable rinse - Econo or Turbo

- Field convertible from straight through to corner and vice versa (kit required)
- Field convertible from 3-phase to single-phase and vice versa (kit required)
- Durable stainless steel construction
- Uses standard 20" X 20" (508 mm X 508 mm) racks
- 1-year parts and labor warranty

\*Racks per hour calculated with NSF suggested load time of five (5) seconds for door-type (straight thru)



Intertek



Intertek



