


A family company manufacturing in the USA

www.glastender.com





Intertek Intertek

4004503

Conforms to NSF/ANSI STD 7 and UL STD 471 Certified to CSA STD C22.2 No. 120 Listed to NSF Standard 7 for open food storage

Standard Features

- · All stainless steel interior with radius corners is easy to keep clean
- · Locking doors
- LED interior lighting
- Heated mullion to minimize condensation
- Evaporator above compressor compartment to maximize storage capacity
- Available without a finished top for integrated installation below customer supplied counter top
- 180° swinging doors

Project:	AIA#	
Item #:	Qty:	SIS#
Model #:		

Coolers, Pass-Thru, One Zone, Front Serviced, Low Profile

CP1FL32, CP1FL36, CP1FL52, CP1FL60, CP1FL72, CP1FL84

CP1FL Configurable Options

Temperature:

- Beer/Food 34°F to 40°F
- White wine 50°F to 55°F
- Red wine 60°F to 65°F

Refrigeration Compartment Location:

Left or Right

Refrigeration Compartment Cover Finish:

- · Black vinyl-clad
- Unlaminated
- Stainless steel
- · Jeweled stainless
- Laminated

Door Style & Finish:

- Door Black vinyl-clad
- Door Unlaminated
- · Door Stainless steel • Door - Jeweled stainless
- · Door Laminated
- · Door Glass, black vinyl-clad
- · Door Glass, stainless steel
- · Door Glass, jeweled stainless
- · Door Glass, laminated

Door Hinge Location (specify for each door):

· Left or Right

Door Handle:

- Polished stainless
- · Polished brass
- · Stainless pull tab

Top Style:

- No finished top
- Stainless top
- Laminated top

Left and Right Side Finish:

- Black vinyl-clad
- · Stainless steel
- Laminated

LED Lighting Style:

- Bright white (7,000k)
- Warm white (3,500k)
- Amber (2,700k)
- · Blue

See our Product Directory for a complete list of cooler accessories

Specifications

Electrical

- 120V, 1 phase, 60 Hz
- Full load amps CP1FL32, CP1FL36 3.0, CP1FL52, CP1FL60, CP1FL72, CP1FL84 - 7.0
- Dedicated 15 amp circuit is required
- Includes a 6 foot NEMA 5-15P grounded cord and plug which exits the back of refrigeration compartment Refrigeration

• R290

- Compressor CP1FL32, CP1FL36 1/8HP, CP1FL52, CP1FL60, CP1FL72, CP1FL84 - 1/4HP
- Heat rejection CP1FL32, CP1FL36 1228 BTU/Hr, CP1FL52, CP1FL60, CP1FL72, CP1FL84 - 2867 BTU/Hr

Operating Range

• 34°F (1°C) to 40°F (4°C)

Plumbing

- · Automatic condensate evaporator. No drain connection required. Shelving
- Two adjustable coated shelves per section included Materials
- Stainless steel parts include: interior, front of cabinet, hinges, hinge and lock brackets, and optional legs
- Black vinyl-clad steel parts include: standard sides, doors and compressor cover
- Galvanized steel parts include: exterior sub-top, back and bottom
- Zinc plated CR steel parts include: leg sockets

Weight Bearing Capacity

Counter tops and other accessories should not exceed 200 pounds per door

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444 www.glastender.com

Specifications subject to change without notice. For current specifications please visit our website.


Approval/Notes:			

Coolers - Pass-Thru, One Zone, Front Serviced, Low Profile


Dimensional Information

PLAN VIEW 16" DOOR OPENING PLAN VIEW 20" DOOR OPENING -12"→ SWING WILL SWING WILL CONTINUE IF NO CONTINUE 18-1/2" DOOR SILL TO DOOR SILL 18-1/2" DOOR SILL TO DOOR SILL IF NO CABINET CABINET TO IMPEDE TO IMPEDE _____ CONDENSING CONDENSING 180° 180° UNIT COMPARTMENT UNIT COMPARTMENT **SWING SWING**


FRONT VIEW 16" DOOR OPENING




FRONT VIEW 20" DOOR OPENING



SIDE VIEW 16" DOOR OPENING






SIDE VIEW 20" DOOR OPENING

WITH OPTIONAL 6" LEGS

6"

SIDE VIEW



Note: Available with compressor left or right. Compressor left model shown.

				Capacities		
16" Door Opening Models	Х	Υ	DOORS	12 oz. bottles, cases	750ml wine bottles*	
CP1FL32	32"	16"	2	4.4	35	
CP1FL52	52"	36"	4	9.7	66	
CP1FL72	72"	56"	6	15.4	106	

				Capacities		
24" Door Models	Х	Y	DOORS	12 oz. bottles, cases	750ml wine bottles*	
CP1FL36	36"	20"	2	5.8	42	
CP1FL60	60"	44"	4	12.7	90	
CP1FL84	84"	68"	6	19.9	137	