



CP1RL48  
 with refrigeration hook-up  
 left, black vinyl-clad doors,  
 and laminated top

### Standard Features

- Remote unit
- All stainless steel interior with radius corners is easy to keep clean
- Locking doors
- LED interior lighting
- Heated mullion to minimize condensation
- Available without a finished top for integrated installation below customer supplied bar top
- 180° swinging doors
- Leg sockets recessed into base
- Stainless steel evaporator housing with separate removable evaporator drain pan

Project: _____	AIA# _____
Item #: _____ Qty: _____	SIS# _____
Model #: _____	

## Coolers

### Pass-Thru, One Zone, Remote, Low Profile

CP1RL24, CP1RL40, CP1RL48,  
 CP1RL60, CP1RL72

### CP1RL Configurable Options

#### Temperature:

- Beer/Food - 34°F to 40°F
- White wine - 50°F to 55°F
- Red wine - 60°F to 65°F

#### Expansion Valve Type:

- R134a/R513A
- R404A/R422A
- R448A/R452A
- R449A
- R407A R407F
- R445A/R450A

#### Refrigeration Hook-Up Location:

- Left or Right

#### Door Style & Finish:

- Door - Black vinyl-clad
- Door - Unlaminated
- Door - Stainless steel
- Door - Jeweled stainless
- Door - Laminated
- Door - Glass, black vinyl-clad
- Door - Glass, stainless steel
- Door - Glass, jeweled stainless
- Door - Glass, laminated

#### Door Hinge Location (specify for each door):

- Left or Right

#### Door Handle:

- Polished stainless
- Polished brass
- Stainless pull tab

#### Top Style:

- No finished top
- Stainless top
- Laminated top

#### Left and Right Side Finish:

- Black vinyl-clad
- Stainless steel
- Laminated

#### LED Lighting Style:

- Bright white (7,000k)
- Warm white (3,500k)
- Amber (2,700k)
- Blue

See our Product Directory for a complete list of cooler accessories.



4004503  
 Conforms to NSF/ANSI STD 7  
 and UL STD 471  
 Certified to CSA STD C22.2 No. 120  
 Meets NSF 7 requirements for open  
 food storage

### Specifications

#### Electrical

- 120V, 1 phase, 60 Hz, 1.5A full load amps
- Dedicated 15 amp circuit is required
- 14 gauge wire connection is made inside the cooler next to evaporator housing - interior access is through one of the 3/4" side knock-out holes (electrician's choice)

#### Refrigeration

- R134a, R404A, R448A, R449A, R422A, R452A, R513A, R407A, R407F, R445A, or R450A expansion valve & temperature control included. Specify type required when ordering.
- Refrigeration system capacity requirements\*: CP1RL24 - 850 BTU/hr, CP1RL40, CP1RL48 - 1,600 BTU/hr, CP1RL60, CP1RL72 - 2,000 BTU/hr
- \* BTU/hr design loads are figured assuming 85° F ambient, 15° F evaporator temperature, all glass doors, maximum internal loading, and average compressor cycling. No solar heat gain has been accounted for.
- All refrigeration hookups are made at the installation site

#### Plumbing

- A six foot length of 1/2" ID by 5/8" OD plastic tubing is provided to drain condensate. The tubing should exit through one of the 3/4" side knock-out holes (installer's choice). The maximum drainage is one ounce per hour - consult local codes for compliance - a floor drain may be required

#### Shelving

- Two adjustable coated shelves per section included

#### Materials

- Stainless steel parts include: interior, front of cabinet, hinges, hinge and lock brackets, and optional legs
- Black vinyl-clad steel parts include: standard sides and doors
- Galvanized steel parts include: exterior sub-top, back and bottom
- Zinc plated CR steel parts include: leg sockets

#### Weight Bearing Capacity

- Counter tops and other accessories should not exceed 200 pounds per door

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780  
 989.752.4275 • 800.748.0423 • Fax 989.752.4444  
[www.glastender.com](http://www.glastender.com)


Approval/Notes:

Specifications subject to change without notice. For current specifications please visit our website.


# Coolers - Pass-Thru, One Zone, Remote, Low Profile

## Dimensional Information

PLAN VIEW 16" DOOR OPENING




PLAN VIEW 20" DOOR OPENING




FRONT VIEW 16" DOOR OPENING

ADD 1" TO HEIGHT FOR FACTORY INSTALLED TOP




FRONT VIEW 20" DOOR OPENING

ADD 1" TO HEIGHT FOR FACTORY INSTALLED TOP




CP1RL24

SIDE VIEW  
16" DOOR OPENING




WITH OPTIONAL 6" LEGS

SIDE VIEW  
20" DOOR OPENING



WITH OPTIONAL 6" LEGS

SIDE VIEW



STANDARD CABINET

STANDARD CABINET

Note: Available with refrigeration hook-up location left or right.

16" Door Opening Models	X	Y	DOORS	Capacities	
				12 oz. bottles, cases	750ml wine bottles
CP1RL40	40"	36"	4	8.2	66
CP1RL60	60"	56"	6	13.8	106

20" Door Opening Models	X	Y	DOORS	Capacities	
				12 oz. bottles, cases	750ml wine bottles
CP1RL24	24"	20"	2	4.7	42
CP1RL48	48"	44"	4	11.8	90
CP1RL72	72"	68"	6	18.3	137



5400 N Michigan Rd • Saginaw, MI • 48604-9780  
989.752.4275 • 800.748.0423 • Fax 989.752.4444  
www.glastender.com

Printed in USA